

Specifications

The Hot Box has many unique features:

- Portable; just pick-up with a forklift
- Built-in spill containment
- Zero-ground clearance available
- 2-year Manufacturer's warranty

Capacity

1 drum (55 gal.), or 1,000 lbs total.

Materials of Construction

All steel construction includes:

- 12 gauge interior walls and 14 gauge exterior walls
- Integrated framing and structural members ensure toughness
- 304 stainless steel construction available

Dimensions

Interior dimensions: 29"W x 28.25"D x 47.5"H Exterior dimensions: 36"W x 36"D x 66.75"H

Insulation

3" thick, 6# density mineral wool

Heating Medium

Steam, hot oil, or hot water

Heat Exchanger

Finned tube heating coil rated for saturated steam up to 200 psig. Recirculating coil available for hot oil or hot water

Temperature Range

Room temperature to 350°F

Spill Containment Pan

14 gallon capacity

Finish

- Exterior finished with acrylic enamel
- Interior finished with heat resistant silver
- Stainless steel available





Steam Hot Box

Model S1

The Benko Products SAHARA HOT BOX drum heaters and ovens are recognized as the industry leader in 55-gallon drum heating equipment. Steam drum heaters are available with state-of-the-art digital controls with independent overtemperature protection. Units in a manifolded arrangement can be individually turned off when not heating, perfect for your drum storage and drum heater needs.

Unit Weight

850 lbs

Installation

Shipped completely assembled.

Set in place and hook up power supply.

Engineering

Custom engineered, computer designed units are available. Contact us for more information.

 $\mbox{\ensuremath{^{*}}}$ Class A ovens available for heating flammables.





Steam Hot Box

Model S1

- 1. STANDARD UNIT WEIGHT: 850 Lbs. (AS SHOWN)
- 2. FINISH: EXTERIOR: ACRYLIC ENAMEL INTERIOR: ALUMINUM-BASED ENAMEL
- 3. HEATING MEDIUM: STEAM HEAT EXCHANGER

 1" SCHED. 40 FINNED TUBE PIPE
 WITH 2" SCHED. 40 HEADERS

 200 PSIG MAX. PRESSURE
- 4. SPILL CONTAINMENT: 14 GALLONS
- 4. SPILL C...

 5. MATERIALS:
 EXTERIOR: HRS, 14 GA. (.075")
 INTERIOR: HRS, 12 GA. (.105")
 INSULATION: 3" X 6# DENSITY MINERAL WOOL
 (ALL WALLS, FLOOR, CEILING AND DOOR)

SELF-ACTING TEMPERATURE CONTROL STEAM TRAP





